



# Slot bracket USB 3.0 pin header 19 pin + SATA 7 pin internal > 1 x Multiport external

## Description

This slot bracket by Delock can be installed into a standard PC slot and expands your system by an external Multiport. The Multiport interface is a combination of USB 3.0 and eSATAp, which provides different connecting options. Thus the Multiport enables you to connect devices, like e.g. Hubs, Card reader, external enclosure etc. with the following interface:

1. USB 3.0
2. USB 2.0
3. eSATAp (Power Over eSATA 5 V)
4. eSATA



Ref.	82978
EAN	4043619829781
Country of origin	China
Customs tariff number	84718000

## Specification

- Connector: internal 1 x 19 pin USB 3.0 pin header female + SATA 7 pin  
external 1 x Multiport female
- Cable gauge: 28 AWG
- Current output: max. 900 mA per each USB port
- Voltage: 5 V
- Data transfer rate up to:  
Super-Speed 5 Gb/s, High-Speed 480 MB/s  
Full-Speed 12 Mb/s, Low-Speed 1.5 Mb/s, eSATA 3 Gb/s
- Downwards compatible to USB 2.0 and USB 1.1
- Cable length: ca. 45 cm (without connector)

### System requirement

- PC with a free slot
- Mainboard with a free 19 pin USB 3.0 pin header connector and a free SATA port

**Note:** For operation of a device which require more than 900 mA you may need to connect an additional power supply for the connected device.

### Package content

- Slot bracket

### Package

- Delock poly bag